



ROLALIGHT[®] 10



August 2022

USER MANUAL

2

2022, JCH DISTRIBUTION ©

SUPPLY INCLUDES :

The ROLALIGHT 10 is delivered in a hard-shell case of 320 X 410 X 170 mm, the whole weighing less than 5 K.



We reserve the right to make changes to the design or specification of this product, which are required to conform with any applicable safety or legal requirements or which do not materially change the quality or performance of the Goods.



Mains plug: specify the model when ordering (EU, UK, etc.)

Charger

PLACING THE ROLALIGHT 10



4 powerful magnets allow attachment to any metal surface, horizontally or vertically.



3

© 2020, JCM DISTRIBUTION



Fixing on a cable tray in a ship passageway...



...or near the ground as emergency

4

PLACING THE ROLALIGHT 10



All positions on a vehicle are possible provided that the bodywork is made of steel...



Below the ROLALIGHT 10 is simply hung on a wooden door and illuminates two rooms...



And here a road sign becomes an area lighting...



FUNCTION

Four levels of light output:

- 1- Maximum output (10,000 lumens): 1 hour working period.
- 2- Half power: (5,000 lumens): 2 hours of working period.
- 3- Minimum power (2,500 lumens): 4 hours of working period.
- 4- Night light (400 lumens): 24 hours of working period.



A quick press on the right or left part of the switch triggers the ignition. Several presses on the right part increase the brightness level.



Several presses on the left part of the switch allow you to decrease the brightness level.



To switch off, maintain pressure on the right part of the switch.

WARNING: After switching off, when rolling up the ROLALIGHT 10 for storage, make sure that accidental triggering cannot occur: risk of overheating...



5

© 2020, JCM DISTRIBUTION

6

© 2020, JCM DISTRIBUTION

RECHARGING BATTERIES

The two side batteries are recharged in 2.5 H to 3 H by the charger connected as shown on the picture on the right. When ordering, specify the type of mains plug that suits you.



Do not use any charger other than the one supplied with your ROLALIGHT 10.

TECHNICAL SHEET

"Smart" Charger: the batteries can remain in permanent charge.

2 year parts and labor warranty. In the event of a breakdown, contact EXPLORCAM : contact details on next page.

ROLALIGHT 10



Dimensions: Unrolled: 1000 X 200 X 60 mm. Rolled up : 220 X 200 X 60 mm
 Weight : 1,85 Kg
 Maximum ambient operating temperature : 40°C. Storage : from 0 to 60°C.
 Power : 130 W (24 V).
 Battery (in 2 side packs) : Lithium Ion 24V 10 Ah.
 Light power : 10 000, 5 000, 2 500 & 400 lumens (dimmer)
 Working period: 1 , 2, 4 and 20 hours. 500 charge/discharge cycles.
 Sealing: IP66
 Fixing by 4 magnets of 11K power or side strap.



Charger

100/240 V => 25,2V 4 Ah. Type of mains plug to be specified when ordering.
 Dimensions : 170 X 72 X 35 mm.
 Weight : 0,5 kg
 Charging period : 2,5 H to 3H depending on ambient temperature.



SAS EXPLORCAM
92 rue des églantiers
34170 CASTELNAU LE LEZ
FRANCE

Tel : 0033 09 66 43 60 36
 Email : jcm.distribution@wanadoo.fr
www.jcmdistribution.com

